

pressure



» **Wide pressure range**

16 pressure ranges, ranging from 25 mbar (0.35 psi) to 700 bar (10,000 psi) F.S. Absolute, differential and gauge sensors.

» **High accuracy**

$\pm 0.025\%$  of reading  $+0.01\%$  F.S.

» **True field calibrator**

Fully temperature compensated

» **Single or dual sensor versions**

Select HPC500 single or HPC502 dual range calibrators and eliminate the need for 2 separate calibrators.

» **Full set of intelligent features**

Wide selection of useful functions and features. Damping, leak test, % error calculation, min/max, switch test, etc.

» **Thermometer**

High accuracy thermometer, Pt100 sensor.

» **External Pressure Modules**

HPC500/502 can be extended with many different pressure modules, with accuracy up to 0.01% F.S.

## Handheld Pressure Calibrator Model HPC500 Family



JOFRA HPC500 calibrators feature deadweight tester accuracy in a modern digital package. The HPC is available as an independent calibrator or in one of 6 ready-for-test systems that are complete and equipped to meet any need for pressure calibration.

The HPC500 may be used in a very broad range of applications from simple tool type jobs to complex calibration jobs in custody transfer systems.

The JOFRA HPC500 calibrators introduce a new generation of AMETEK handheld pressure calibrators. This series has been designed to meet high accuracy pressure calibration applications and facilitate your tasks. The HPC offers features such as user configurable information display, 15 different pressure units, transmitter supply, mA input, % error calculation, voltage measurement, serial communication, and external pressure module capability. The accuracy of the HPC500 calibrators is specified in % of reading to ensure an even better accuracy and wider applicable pressure range. The HPC is temperature compensated from 0 to 50°C / 32 to 122°F for on-site operation. It is a truly superior pressure calibrator for laboratory and field use, bringing laboratory accuracy into the field.

The JOFRA APM series of pressure modules extends the application base of the HPC calibrators by allowing calibrations in additional ranges. The APM modules are compatible with several other JOFRA calibrators.

Calibration of the instrument may be performed locally without returning the HPC unit to the manufacturer. Adjustment software is part of the design - you just need an accurate pressure reference and a PC. If factory calibration is required, the pump and the calibrator are independent units and only the calibrator needs to be returned.

ISO 9001 Manufacturer

Specification Sheet  
SS-HPC500

**AMETEK®**  
TEST & CALIBRATION INSTRUMENTS

### Clear graphical display

Large backlit graphical display shows current status and mode, 1, 2 or 3 measurement windows, to suit your applications and demands.

### Intuitive menu system

Combination of “soft keys” and cursor keypad ensures easy operation

### Serial interface

Connection for JOFRA APM pressure module and computer.



### Zero

To keep high accuracy, a dedicated zero button is available to provide convenient zero before test.

### Electrical connections

HPC calibrators are well equipped and include inputs for mA, voltage, switches and temperature measurements, including 24 VDC supply for mA transmitters.

### Full set of features

Perform semi-automatic pressure switch tests, leak test, % error calculation, switch in HART resistor or other calibration tasks through the outstanding functions and features of the HPC500.

### Temperature measurement

High accuracy temperature measurement port by use of the optional Pt100 sensor. A superb instrument for easy and convenient temperature measurement.

### Pressure connections

1/8" BSP female. 300 series stainless steel.  
1/4" NPT male and 1/4" BSP female adapters are supplied as standard.

### ON / OFF

Auto shut-off to expand battery life time (user programmable).

### Units

15 different engineering units on pressure measurements.



### JOFRA APM pressure module

The JOFRA APM external pressure modules extend the range of the JOFRA HPC. There are many models available with gauge, absolute, differential, and vacuum pressure references, in metric and imperial engineering units.

The modules are engineered for in-plant, field, or laboratory use. They are ready-to-use with the JOFRA HPC and the protocol allows for immediate recognition and use of the module once it is plugged into the calibrator.

APM Mk.II Type	Pressure range				12 month accuracy	
	Bar		PSI		%rdg	%FS
	From	To	From	To		
<b>Differential</b>						
025MD	-0.025	0.025	-0.4	0.4	-	0.100%
075MD	-0.070	0.07	-1	1	-	0.050%
350MD	-0.350	0.35	-5	5	-	0.050%
<b>Compound</b>						
001C	-0.960	1	-14	15	0.025%	0.010%
002C	-0.960	2	-14	30	0.025%	0.010%
007C*	-0.820	7	-12	100	0.025%	0.010%
020C*	-0.820	20	-12	300	0.025%	0.010%
035C*	-0.820	35	-12	500	0.025%	0.010%
<b>Gauge</b>						
001G*	0	1	0	15	0.025%	0.010%
002G*	0	2	0	30	0.025%	0.010%
007G*	0	7	0	100	0.025%	0.010%
020G*	0	20	0	300	0.025%	0.010%
035G*	0	35	0	500	0.025%	0.010%
070G*	0	70	0	1000	0.025%	0.010%
100G*	0	100	0	1500	0.025%	0.010%
200G*	0	200	0	3000	0.025%	0.010%
350G*	0	350	0	5000	0.025%	0.010%
400G*	0	400	0	6000	0.025%	0.010%
700G*	0	700	0	10000	0.025%	0.015%
<b>Absolute</b>						
001A	0.025	1.1	0.35	16	0.025%	0.010%
003A	0.025	3.5	0.35	50	0.025%	0.010%
007A*	0.070	7	1	100	0.025%	0.010%
020A*	0.070	20	1	300	0.025%	0.010%

\* Stainless steel isolated pressure sensor

Specified temperature range 23°C ± 5°C / 73°F ± 9°F

F.S. (full scale) is the numerical value of the positive pressure range. Accuracy includes hysteresis, nonlinearity, repeatability and reference standard uncertainty, 1 Year typical long-term stability, operated inside the rated temperature span and pressure range. Requiring frequently zeroing (Gauge/diff.) or entering of reference pressure (Absolute).



## FUNCTIONAL SPECIFICATIONS

### Pressure; gauge / compound ranges

bar	..... -0.96 to 1 & 2
psi	..... -14 to 15 & 30
bar	..... -0.82 to 7, 20 & 35
psi	..... -12 to 100, 300 & 500

### Pressure; gauge

bar	..... 70, 200, 350 & 700
psi	..... 1,000, 3,000, 5,000 & 10,000

### Pressure; absolute ranges

bar	..... 0.025 to 1.1 & 2
psi	..... 0.35 to 16 & 30
bar	..... 0.07 to 7 & 20
psi	..... 1 to 100 & 300

### Pressure; differential ranges (HPC500 only)

mbar	..... ±25, ±70 & ±350
psi	..... ±0.35, ±1 & ±5

### Engineering units (built-in)

User selectable..... 15 units  
 (bar, mbar, MPa, kPa, inHg@0°C, mmHg@0°C, kg/cm², mmH₂O@4°C, mmH₂O@20°C, psi, inH₂O@4°C, inH₂O@20°C, inH₂O@60°F, cmH₂O@4°C, cmH₂O@20°C)

### Pressure accuracy ambient temp. (18 to 28°C / 65 to 82°F)

±25 mbar / 0.35 psi	..... ±0.10% F.S.
±70, 350 mbar / 1, 5 psi	..... ±0.05% F.S.
700 bar / 10K psi	..... ±0.025% RDG + 0.015% F.S.
All other pressure ranges	..... ±0.025% RDG + 0.01% F.S.
Vacuum	..... ±0.025% F.S.

F.S. (full scale) is the numerical value of the positive pressure range.

Accuracy includes hysteresis, nonlinearity, repeatability and reference standard uncertainty, 1 Year typical long-term stability, operated inside the rated temperature span and pressure range.

Requiring frequently zeroing (Gauge/diff.) or entering of reference pressure (Absolute).

### Pressure accuracy ambient temp. (0 to 50°C / 32 to 122°F)

±25 mbar / 0.35 psi	..... ±0.15% F.S.
±70, 350 mbar / 1, 5 psi	..... ±0.10% F.S.
700 bar / 10K psi	..... ±0.04% RDG + 0.015% F.S.
All other pressure ranges	..... ±0.04% RDG + 0.01% F.S.
Vacuum	..... ±0.05% F.S.

F.S. (full scale) is the numerical value of the positive pressure range.

Temperature effect -10 to 0°C / 14 to 32°F ±0.005% F.S./°C.

Accuracy includes hysteresis, nonlinearity, repeatability and reference standard uncertainty, 1 Year typical long-term stability, operated inside the rated temperature span and pressure range.

Requiring frequently zeroing (Gauge/diff.) or entering of reference pressure (Absolute).

### Display

LCD	..... Graphical (with light)
Display resolution	..... 5 digits
Display update	..... 3 times per second

### RS232 communication interface

Connector	..... LEMO
Serial	..... 0-5 VDC, 9600 baud, 8 data, no parity, 1 stop
Protocol	..... ASCII command language

### Input / output (18 to 28°C / 65 to 82°F)

mA range	..... 0 to 24 mA
mA accuracy	..... ±0.015% RDG + 2 µA
Transmitter supply	..... 24 VDC ±10%
Voltage measurement	..... 0 to 30 VDC
Voltage accuracy	..... ±0.015% RDG + 2mV
RTD range (ohms)	..... 84 to 140 Ω
RTD accuracy	..... ±0.015% RDG + 0.02 Ω
RTD range (temperature)	..... -40 to 150°C / -40 to 302°F
RTD accuracy @ 0°C/32°F (temperature)	..... ±0.10°C / 0.18°F
HART® resistor	..... 250 Ω
Peak hold capture	..... 50 milliseconds
Switch test input	..... 5V (<1mA)

Temperature effect outside 18 to 28°C / 65 to 82°F ±0.001% F.S./°C.

### Media compatibility

Nickel plated brass and 316 stainless steel

### Environmental

Operating temperature	..... -10 to 50°C / 14 to 122°F
Storage temperature	..... -20 to 60°C / -4 to 140°F
Ingress protection rating	..... IP54

### Pressure connection

All calibrators ..... 1/8" BSP female  
 Adapters to 1/4" NPT male and 1/4" BSP female are included as standard.

### Pressure overload

Overload alarm..... "OL" in display at approx. +20% F.S.

### Power supply

Battery	..... 4 x 1.5 VDC Alkaline
Battery type	..... AA, LR6, MN1500, AM3
Battery lifetime	..... Typically more than 35 hours
Low battery indicator	..... Yes

### Instrument dimensions (LxWxH)

Calibrator	..... 201x99x50 mm / 8.3x3.9x2.0 in
HPC500 weight (incl. battery)	..... 635 g / 22.4 oz
HPC502 weight (incl. battery)	..... 665 g / 23.5 oz
Calibrator, shipping	..... 243x180x80 mm / 9.6x7.1x3.1 in
Calibrator weight, shipping	..... 1.1 kg / 39.5 oz

### Miscellaneous

Compliance: EN 61326 : 2006 & CISPR 11, Edition 5.0 - 2009 Class "B"



Function / Feature	HPC500	HPC502
Single sensor high accuracy pressure calibrator	✓	✗
Dual sensor high accuracy pressure calibrator	✗	✓
mA measurement	✓	✓
Voltage measurement	✓	✓
24 VDC transmitter supply	✓	✓
High speed pressure switch test	✓	✓
Temperature measurement with external RTD sensor	✓	✓
JOFRA APM pressure module connection	✓	✓
RS232 communication	✓	✓
On-line calculation of sensor error %	✓	✓
Automatic leak test timer function	✓	✓
High speed min./max. hold	✓	✓
Delta / sum calculation on pressure measurements	✓	✓
Display contrast adjustment	✓	✓
Instrument setup lock	✓	✓
Storage of 5 setups	✓	✓
Setup of automatic off timer	✓	✓
Setup of number of display windows / measurement channels	✓	✓
Setup of temperature sensor RTD type	✓	✓
Select display high or low resolution	✓	✓
Setup of backlight timer	✓	✓
HART resistor on/off	✓	✓
Normal or dampened display update rate	✓	✓



## JOFRACAL CALIBRATION SOFTWARE

JOFRACAL calibration software ensures easy calibration of RTD's, thermocouples, transmitters, thermoswitches, pressure gauges and pressure switches. JOFRACAL can be used with all JOFRA calibration instruments. When used with ASM-800 signal multi scanner, JOFRACAL can perform a simultaneous semi automatic calibration on up to 24 pressure and/or temperature devices under test in any combination.

JOFRACAL software controls the complete calibration procedure, stores the results and provides a calibration audit trail through hard-copy certificates. All calibration data are stored for each sensor to monitor drift and optimise recalibration intervals. A scheduler feature allows planning of future calibrations.

## HPC500 PRESSURE RANGES

This table shows the resolutions that can be obtained by the HPC calibrators throughout all engineering units.

<b>HPC500/HPC502 Ranges and Resolutions</b>													
Range (bar)	25mbar	70mbar	350mbar	1	1.1	2	7	20	35	70	200	350	700
Burst pressure (bar)	1.4	1.4	7	20	20	20	70	133	133	677	677	677	1000
Proof pressure (bar)	70mbar	200mbar	1	2	2	4	14	40	67	200	400	677	1000
Static pressure (bar)	70mbar	7	7	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Range (psi)	0.35	1	5	15	16	30	100	300	500	1000	3000	5000	10000
Burst pressure (psi)	10	10	100	300	300	300	1000	2000	2000	10000	10000	10000	15000
Proof pressure (psi)	1	3	15	30	30	60	200	600	1000	3000	6000	10000	15000
Static pressure (psi)	1	100	100	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
psi	0.4000	1.0000	5.0000	15.000	16.000	30.000	100.00	300.00	500.00	1000.00	3000.00	5000.00	10000.00
bar	0.0689	0.0689	0.3447	1.0342	1.1032	2.0684	6.8947	20.684	34.474	68.947	206.84	344.74	689.47
mbar	27.579	68.948	344.74	1034.2	1103.2	2068.4	6894.8	20684	344.74	689.48	n/a	n/a	n/a
kPa	2.7579	6.8948	34.474	103.42	110.32	206.84	689.48	2068.4	3447.4	6894.8	2068.4	3447.4	6894.8
MPa	0.0028	0.0068	0.0344	0.1034	0.1103	0.2068	0.6894	2.0684	3.447	6.8948	20.684	34.474	68.948
kg/cm <sup>2</sup>	0.0281	0.0703	0.3515	1.0546	1.1248	2.1092	7.0307	21.092	35.153	70.307	210.92	351.53	703.07
cmH <sub>2</sub> O@4°C	28.124	70.309	351.54	1054.6	1124.9	2109.3	7030.9	21093	35154	70309	n/a	n/a	n/a
cmH <sub>2</sub> O@20°C	28.173	70.434	352.17	1056.5	1126.9	2113.0	7043.4	21130	35217	70434	n/a	n/a	n/a
mmH <sub>2</sub> O@4°C	281.24	703.09	3515.4	10546	11249	21093	70309	n/a	n/a	n/a	n/a	n/a	n/a
mmH <sub>2</sub> O@20°C	281.73	704.34	3521.7	10565	11269	21130	70434	n/a	n/a	n/a	n/a	n/a	n/a
inH <sub>2</sub> O@4°C	11.072	27.681	138.40	415.21	442.89	830.42	2768.1	8304.2	13840	27681	83042	n/a	n/a
inH <sub>2</sub> O@20°C	11.092	27.730	138.65	415.95	443.68	831.89	2773.0	8318.9	13865	27730	83189	n/a	n/a
inH <sub>2</sub> O@60°F	11.083	27.708	138.54	415.61	443.32	831.23	2770.8	83123	13854	27708	83123	n/a	n/a
mmHg@0°C	20.686	51.715	258.58	775.73	827.44	1551.5	5171.5	15515	25858	51715	n/a	n/a	n/a
inHg@0°C	0.8144	2.0360	10.108	30.540	32.576	61.081	203.6	610.81	1018.0	2036.0	6108.1	10180	20360

Proof pressure - maximum allowable pressure without a shift in calibration.

Burst pressure - sensor damaged or destroyed, some risk of personal injury.

Static pressure - Differential units only. Maximum allowed common mode pressure between both points.

Compound ranges - the data for the 1 bar range also applies to the -1 to +1 bar compound range, the data for the 2 bar range also applies to the -1 to +2 bar compound range.

Absolute ranges - the data for the 1.1, 2, 7 and 20 bar ranges also applies to the absolute pressure versions of those ranges.

## STANDARD DELIVERY (HPC Calibrator)

- HPC500 or HPC502 calibrator
- Traceable calibration certificate (NIST) with pressure and vacuum calibration points
- 4 x 1.5 volt batteries
- Adapter to 1/4" NPT male from 1/8" BSP male\*
- Adapter to 1/4" BSP female from 1/8" BSP male\*
- 1/8" sealed gasket / washer type
- Test leads: red and black
- Hand strap with clip
- User manual

\* Set for each pressure port



### HPC500, System A

- AXX/0 to 2 bar (0 to 30 psi)
- AHX/0 to 40 bar (0 to 580 psi)



This system includes the HPC calibrator together with one pneumatic hand pump: T-960 and T-970, depending on the chosen pressure range. System A is an easy-to-use single hand operated calibration system. No need for a flat surface to operate the system - just hold it in your hand.

The system comes in a carrying case with cut-outs for fittings, hose, and the complete assembled calibration unit - no time is required to assemble the unit. The calibrator can at any time be used separately for other pressure test jobs.

A special quick connector between the pump and the calibrator makes it possible to separate the system in seconds and swivel the calibrator for easy viewing.

The HPC calibrators used in System A are delivered calibrated in both pressure and vacuum.

#### T-960 and T-970 pumps for system A

Model T-960 pneumatic pressure pump features an extended range volume adjuster for precise control of the pump pressure and a comfortable pistol grip handle.

Model T-970 pneumatic pressure pump is similar to the T-960, but generates pressures up to 40 bar (580 psi).

Pressure range, T-960.....	0 to 2 bar (30 psi)
Pressure range, T-970.....	0 to 40 bar (580 psi)
Type.....	Pneumatic
Test medium.....	Air
Operation.....	Scissor
"O"-rings .....	Buna-N
Wetted parts.....	Aluminum, brass, stainless steel, nylon, Nylatron GS
Connection to test object.....	Hose 0.6 m/24 in with 1/4" BSP and NPT female terminations
Size.....	21.6x12.1x6.2 cm / 8.5x4.8x2.4 in
Total system weight .....	5.5 kg / 12.2 lb

#### Included with System A delivery

- HPC standard delivery (see page 6)
- Hand pump T-960 or T-970 with a 0.6 m / 24 in hose with 1/4" BSP and NPT female terminations
- 3/8" BSP female adapter with 1/4" BSP and NPT female terminations
- Quick connector between pump and HPC calibrator
- 1 roll of Teflon tape
- Protective carrying case

#### Accessories

- Pressure hose for T-960/970, 0.5 meter
- Pressure hose for T-960/970, 1.0 meter
- Pressure hose for T-960/970, 2.0 meter
- Pressure hose for T-960/970, 5.0 meter
- Set of BSP female fittings, Teflon tape, packings  
\* Fitting size : 1x1/8", 1x3/8", 1x1/2"
- Set of NPT female fittings, Teflon tape, packings  
\* Fitting size : 1x1/8", 1x1/4", 1x3/8" 1x1/2"
- Connections for APM H/S pressure modules
- Fitting 1/8" NPT male to 1/4" NPT male for APM-H pressure module
- Fitting 1/4" NPT male to 1/4" NPT male for APM-S pressure module

### HPC500, System B

- BXX/-0.91 to 2 bar (30 psi)
- BHX/-0.91 to 40 bar (580 psi)



This system includes the dual function pneumatic hand pump. With this pump you can calibrate both vacuum and pressure applications. It takes just a few seconds to switch between vacuum and pressure, just push one button (valve) on the T-965 or T-975 hand pump.

The System B comes in a carrying case with cut-outs for fittings, hose and the complete assembled calibration unit - no time required to assemble the unit before use.

The calibrator and the pump are fitted with a special quick connector that makes it possible to separate the system in seconds without any tool. This quick connector also makes it possible to use the assembled system with the calibrator twisted to any angle.

#### T-965 and T-975 hand pumps for system B

Model T-965 and T-975 pneumatic pressure pumps feature both vacuum and pressure generation. A quick switch (valve) makes it easy to switch from vacuum to pressure measurement. A built-in release valve, volume adjuster for fine adjustment and dual pressure output enable a safe and simple operation. The unit offers both metric and imperial threads on the reference connection and the hose.

Press. range, T-965.....	-0.65 bar (-9.4 psi) to 2 bar (30 psi)
Press. range, T-975....	-0.91 bar (-13 psi) to 40 bar (580 psi)
Type.....	Pneumatic
Test medium.....	Air
Operation.....	Scissor
"O"-rings .....	Buna-N
Wetted parts.....	Aluminum, brass, stainless steel, nylon, Nylatron GS
Connection to test object.....	Hose 0.6 m/24 in with 1/4" BSP and NPT female terminations
Size.....	21.6x12.1x6.2 cm / 8.5x4.8x2.4 in
Total system weight .....	5.5 kg / 12.2 lb

#### Included with System B delivery

- HPC standard delivery (see page 6)
- Hand pump T-965 or T-975 with a 0.6 m / 24 in hose with 1/4" BSP and NPT female terminations
- 3/8" BSP female adapter with 1/4" BSP and NPT female terminations
- Quick connector between pump and calibrator
- 1 roll of Teflon tape
- Protective carrying case

#### Accessories

- Pressure hose for T-975, 0.5 meter
- Pressure hose for T-975, 1.0 meter
- Pressure hose for T-975, 2.0 meter
- Pressure hose for T-975, 5.0 meter
- Set of BSP female fittings, Teflon tape, packings  
\* Fitting size : 1x1/8", 1x3/8", 1x1/2"
- Set of NPT female fittings, Teflon tape, packings  
\* Fitting size : 1x1/8", 1x1/4", 1x3/8" 1x1/2"
- Connections for APM H/S pressure modules
- Fitting 1/8" NPT male to 1/4" NPT male for APM-H pressure module
- Fitting 1/4" NPT male to 1/4" NPT male for APM-S pressure module



## HPC500, System C

- CXX/0 to 200 bar (3,000 psi)
- CHX/0 to 350 bar (5,000 psi)



This system consists of an HPC calibrator together with a hydraulic, high pressure hand pump T-620 or T-620H featuring an oil reservoir to prime the system.

System C is an easy-to-use single hand-operated calibration system. No need for a flat surface (table) to operate the system. The system includes release valve and volume adjuster for fine adjustment to enable a safe and simple operation of the pump.

The System C comes in a carrying case with cut-outs for fittings, hose, and the complete assembled calibration unit - no time adder to assemble the unit before use. Easy and fast connection between pump and calibrator makes it easy to use the pressure calibrator separately for other pressure test jobs.

### AMETEK hydraulic hand pump for system C

This easy-to-use hand pump is specially designed for high pressure applications. The pump has a built-in reservoir, vent valve, and volume adjuster for fine adjustment. The pump has a dual pressure output - one for the test object and one for the HPC calibrator.

Pressure range, T-620.....	0 to 200 bar (3,000 psi)
Pressure range, T-620H.....	0 to 350 bar (5,000 psi)
Type.....	Hydraulic
Test medium.....	Oil
Operation.....	Scissor
Reservoir capacity.....	200 ml / 0.42 pint
Operation.....	Pistol-grip
"O"-rings .....	Buna-N
Wetted parts.....	Aluminum, brass, stainless steel, Lexan
Connection to test object.....	Hose 0.6 m/24 in with 1/4" BSP and NPT female terminations
Size.....	21.6x12.1x6.2 cm / 8.5x4.8x2.4 in
Total system weight .....	5.5 kg / 12.2 lb

### Included with System C delivery


- HPC standard delivery (see page 6)
- Hand pump T-620 or T-620H with a 0.6 m / 24 in hose with 1/4" BSP and NPT female terminations
- 1 roll of Teflon tape
- Protective carrying case

### Accessories

- Pressure hose for T-620/T-620H pumps
- 1 m hose with 1/4" BSP female termination  
Max. pressure 350 bar (5,000 psi)
- 2 m hose with 1/4" BSP female termination  
Max. pressure 350 bar (5,000 psi)
- Oil for T-620 & T-1 pump AAA OIL in 1-QUART CAN
- Oil for T-620 & T-1 pump AAA OIL in 1-GALLON CAN
- Connections for APM H/S pressure modules
- Fitting 1/8" NPT male to 1/4" NPT male for APM-H pressure module with system C
- Fitting 1/8" NPT male to 1/8" NPT male for APM-H pressure module with system C
- Fitting 1/8" NPT male to 1/4" NPT male for APM-H pressure module
- Fitting 1/4" NPT male to 1/4" NPT male for APM-S pressure module

## HPC500, System D

- DOX/0 to 350 bar (5,000 psi) oil
- DWX/0 to 350 bar (5,000 psi) water



This system consists of an HPC calibrator with a hydraulic, high pressure screw pump. System D is an easy-to-use calibration system. Place the pump on a flat surface and turn the handle to generate pressure. The calibrator may be adjusted to give the best viewing angle. The system includes a manifold for connection of the test device, a fine adjustment volume adjuster (optional), and a reservoir for extra oil or water (optional).

The system comes in a carrying case with cut-outs for fittings and the complete assembled calibration unit - no time adder to assemble the unit before use. Easy and fast connection between pump and calibrator makes it easy to use the pressure calibrator separately for other pressure test jobs.

### AMETEK spindle pump for system D

The spindle pumps are designed for easy generation of high pressure. The spindle pumps have a 4-connection manifold. Fine adjustment, extra fine volume adjuster, liquid reservoir, and fittings are optional. Spindle pumps may be delivered for 2 different test media: hydraulic oil or water.

Pressure range .....	0 to 350 bar (5,000 psi)
Type.....	Hydraulic
Test medium.....	Hydraulic oil, water
Operation.....	Spindle pump
Reservoir capacity.....	250 ml / 0.53 pint
"O"-rings .....	Buna-N
Wetted parts.....	Aluminum, brass, stainless steel
Connection to test object.....	4 x 1/4" BSP female
Size.....	36.6x19.5x10.5 cm / 14.4x7.7x4.1 in
Total system weight .....	11 kg / 24.3 lb

### Included with System D delivery

- HPC standard delivery (see page 6)
- Spindle pump for hydraulic oil or for water
- 10 x 1/4" bonded seals
- Allen key 6 mm
- 2 x 1/4" NPT female adapters
- 1 roll of Teflon tape
- Protective carrying case

### Accessories

- Extra fine adjuster, volume adjuster
- Reservoir set with seals, valve and bonded seal
- 1 m Pressure hose (Max. 350 bar / 5,000 psi)<sup>1</sup>
- 2 m Pressure hose (Max. 350 bar / 5,000 psi)<sup>1</sup>
- 1.5 m Pressure hose (Max. 700 bar/10,000psi)<sup>1</sup>
- 5 m Pressure hose (Max. 700 bar / 10,000 psi)<sup>1</sup>
- Extension tube 120 mm (Max. 350 bar/5,000 psi)<sup>1</sup>
- Quick connector set, female 1/4" BSP to 1/4" BSP
- Connections for APM H/S pressure modules
- Fitting 1/4" BSP male x 1/4" BSP male for APM-S pressure module with system D
- Fitting 1/4" BSP male to 1/4" NPT female for APM-H pressure module with system D
- Fitting 1/8" NPT male to 1/4" NPT male for APM-H pressure module with system D
- Fitting 1/4" NPT male to 1/4" BSP female for APM-S pressure module with spindle pump alone
- Fitting 1/8" NPT male to 1/4" BSP female for APM-H pressure module with screw pump alone

<sup>1</sup> 1/4" BSP female to 1/4" BSP male





## ORDERING INFORMATION

Order number						Description
HPC						Type
	500					Model
	NONE					No calibrator, pressure system only
						Pressure range
		25MD				±25 mbar / 0.35 psi differential
		70MD				±70 mbar / 1 psi differential
		350MD				±350 mbar / 5 psi differential
		001A				0.025 bar / 0.35 psi to 1.1 bar / 16 psi absolute
		001C				-0.96 bar / -14 psi to 1 bar / 15 psi gauge/compound
		002A				0.025 bar / 0.35 psi to 2 bar / 30 psi absolute
		002C				-0.96 bar / -14 psi to 2 bar / 30 psi gauge/compound
		007A				0.070 bar / 1 psi to 7 bar / 100 psi absolute
		007C				-0.82 bar / -12 psi to 7 bar / 100 psi gauge/compound
		020A				0.070 bar / 1 psi to 20 bar / 290 psi absolute
		020C				-0.82 bar / -12 psi to 20 bar / 290 psi gauge/compound
		035C				-0.82 bar / -12 psi to 35 bar / 500 psi gauge/compound
		070G				0 to 70 bar / 1,000 psi gauge
		200G				0 to 200 bar / 2,900 psi gauge
		350G				0 to 350 bar / 5,000 psi gauge
		700G				0 to 700 bar / 10,000 psi gauge
						Calibration certificate
			G			NIST traceable calibration certificate
						Accessories (Optional)
				B		Rechargeable battery pack
				C		Soft case
				I		Interface Kit LEMO to RS232
				T		Temperature sensor Pt100
						Pressure system
					IND	Calibrator only
					AXX	Syst. A, T-960 pump ranges up to 2 bar/30 psi
					AHX	Syst. A, T-970 pump ranges up to 35 bar/500 psi
					BXX	Syst. B, T-965 pump ranges up to 2 bar/30 psi
					BHX	Syst. B, T-975 pump ranges up to 35 bar/500 psi
					CXX	Syst. C, T-620 pump ranges up to 200 bar/2,900 psi OIL
					CHX	Syst. C, T-620H pump ranges up to 350 bar/5,000 psi OIL
					DOX	Syst. D, 65-P016 pump ranges up to 350 bar/5,000 psi OIL
					DWX	Syst. D, 65-P017 pump ranges up to 350 bar/5,000 psi WATER
					EXX	Syst. E, 65-P014 pump ranges up to 700 bar/10,000 psi OIL
					FWB	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi WATER/Buna-N
					FWV	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi WATER/VITON
					FWE	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi WATER/EPT
					FOB	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi OIL
					FOV	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi OIL/VITON
					FOE	Syst. F, T.1 pump ranges up to 700 bar/10,000 psi OIL/EPT
						Sample order number
HPC	500	035C	G	BCIT	BHX	HPC500, -0.82 to 35 bar, NIST traceable certificate, rechargeable battery package, soft case, interface kit, temperature sensor, system B T-975 pump

## ORDERING INFORMATION

Order number						Description	
HPC						Type	
	502					Model	
	NONE					No calibrator, pressure system only	
		Port 1	Port 2	Pressure range (Port 1 - lowest pressure, Port 2 - highest pressure)			
		001A	001A	0.025 bar / 0.35 psi to 1.1 bar/ 16 psi absolute			
		001C	001C	-0.96 bar / -14 psi to 1 bar / 15 psi gauge/compound			
		002A	002A	0.025 bar / 0.35 psi to 2 bar /30 psi absolute			
		002C	002C	-0.96 bar / -14 psi to 2 bar / 30 psi gauge/compound			
		007A	007A	0.070 bar / 1 psi to 7 bar / 100 psi absolute			
		007C	007C	-0.82 bar / -12 psi to 7 bar / 100 psi gauge/compound			
		020A	020A	0.070 bar / 1 psi to 20 bar /290 psi absolute			
		020C	020C	-0.82 bar / -12 psi to 20 bar / 290 psi gauge/compound			
		035C	035C	-0.82 bar / -12 psi to 35 bar / 500 psi gauge/compound			
		070G	070G	0 to 70 bar / 1,000 psi gauge			
		200G	200G	0 to 200 bar / 2,900 psi gauge			
		350G	350G	0 to 350 bar / 5,000 psi gauge			
		700G	700G	0 to 700 bat / 10,000 psi gauge			
					Calibration certificate		
				G	NIST traceable calibration certificate		
					Accessories (Optional)		
					B	Rechargeable battery pack	
					C	Soft case	
					I	Interface Kit LEMO to RS232	
					T	Temperature sensor Pt100	
					Pressure system		
					IND	Calibrator only	
					AXX	Syst. A, T-960 pump ranges up to 2 bar/30 psi	
					AHX	Syst. A, T-970 pump ranges up to 35 bar/500 psi	
					BXX	Syst. B, T-965 pump ranges up to 2 bar/30 psi	
					BHX	Syst. B, T-975 pump ranges up to 35 bar/500 psi	
					CXX	Syst. C, T-620 pump ranges up to 200 bar/2,900 psi OIL	
					CHX	Syst. C, T-620H pump ranges up to 350 bar/5,000 psi OIL	
					DOX	Syst. D, 65-P016 pump ranges up to 350 bar/5,000 psi OIL	
					DWX	Syst. D, 65-P017 pump ranges up to 350 bar/5,000 psi WATER	
					EXX	Syst. E, 65-P014 pump ranges up to 700 bar/10,000 psi OIL	
					FWB	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi WATER/Buna-N	
					FWV	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi WATER/VITON	
					FWE	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi WATER/EPT	
					FOB	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi OIL	
					FOV	Syst. F, T-1 pump ranges up to 700 bar/10,000 psi OIL/VITON	
					FOE	Syst. F, T.1 pump ranges up to 700 bar/10,000 psi OIL/EPT	
					Sample order number		
HPC	502	035C	350G	G	BCIT	BHX	HPC502, port 1: -0.82 to 35 bar, port 2: 0 to 350 bar, NIST traceable certificate, rechargeable battery package, soft case, interface kit, temperature sensor, system B T-975 pump

## ACCESSORIES

### Rechargeable battery kit - Option B

The HPC500 is available with a set of 4 rechargeable AA batteries and a charger.

### Useful soft case - Option C

The HPC500 can be delivered with a soft case as an option. The handy soft case is designed for protection during transport. The soft case has separate compartments for HPC500 (w/Velcro strap), test leads, test hoses, temperature probe, and JOFRA APM pressure module. A shoulder strap ensures convenient transportation when climbing ladders, etc. and the handy strap on the back makes it possible to hang the instrument on a valve, ladder etc. The manual and calibration documents fit into a pocket on the front of the soft case.

### Interface kit - Option I

Special LEMO to Sub D, RS232 interface cable for HPC500 and HPC502.

### Temperature sensor - Option T

To utilize the thermometer utility of the HPC500 family, a ruggedized handheld temperature sensor is available. The sensor comes as a ready-to-use probe with handle and coiled cable with LEMO connector for HPC500 and HPC502. The sensor is built with a high accuracy Pt100 element, accuracy  $\pm 0.05^{\circ}\text{C}$  /  $\pm 0.27^{\circ}\text{F}$ . Sensor dimensions, without handle and cable,  $\varnothing$  4x200 mm/stainless steel.

### Complete calibration systems

The HPC500 is available as a calibrator only or one of 6 ready-for-test systems that are complete and equipped to meet your pressure calibration needs.



Option C



#### AMETEK Test & Calibration Instruments

A business unit of AMETEK Measurement & Calibration Technologies Division offering the following industry leading brands for test and calibration instrumentation.

#### JOFRA Calibration Instruments

##### Temperature Calibrators

Portable dry-block calibrators, precision thermometers and liquid baths. Temperature ranges from  $-90^{\circ}\text{C}$  ( $-130^{\circ}\text{F}$ ) to  $1205^{\circ}\text{C}$  ( $2200^{\circ}\text{F}$ ). Temperature sensors for industrial and marine use.

##### Pressure Calibrators

Convenient electronic systems ranging from  $-25$  mbar to 1000 bar - fully temperature-compensated for problem-free and accurate field use.

##### Signal Instruments

Process signal measurement and simulation for easy control loop calibration and measurement tasks.

#### M&G Pressure Testers & Pumps

Pneumatic floating-ball or hydraulic piston dead weight testers with accuracies to 0.015% of reading. Pressure generators delivering up to 1,000 bar.

#### Lloyd Instruments

Materials testing machines and software from Lloyd Instruments guarantees expert materials testing solutions. The comprehensive program also covers Texture Analysers to perform rapid, general food testing and detailed texture analysis on a diverse range of foods and cosmetics.

#### Davenport Polymer Test Equipment

Allows measurement and characterization of moisture-sensitive PET polymers and polymer density.

#### Chatillon Force Measurement

The hand held force gauges and motorized testers have earned their reputation for quality, reliability and accuracy and they represent the de facto standard for force measurement.

#### Newage Testing Instruments

Hardness testers, durometers, optical systems and software for data acquisition and analysis.

**AMETEK®**  
TEST & CALIBRATION INSTRUMENTS

**UK**  
AMETEK Calibration Instruments  
Tel +44 (0)1243 833 302  
jofra@ametek.co.uk

**France**  
AMETEK S.A.S.  
Tel +33 (0)1 30 68 89 40  
general.lloyd-instruments@ametek.fr

**Germany**  
AMETEK GmbH  
Tel +49 (0)2159 9136 510  
info.mct-de@ametek.de

**Denmark**  
AMETEK Denmark  
Tel +45 4816 8000  
jofra@ametek.com

**USA**  
AMETEK Mansfield & Green  
Tel +1 (800) 527 9999  
cal.info@ametek.com

**India**  
AMETEK Instruments India Pvt Ltd.  
Tel +91 22 2836 4750  
jofra@ametek.com

**Singapore**  
AMETEK Singapore Pte Ltd  
Tel +65 6484 2388  
jofra@ametek.com

**China**  
AMETEK Inc. - Shanghai  
Tel +86 21 5868 5111  
AMETEK Inc. - Beijing  
Tel +86 10 8526 2111

AMETEK Inc. - Guangzhou  
Tel +86 20 8363 4768  
jofra.sales@ametek.com.cn

[www.jofra.com](http://www.jofra.com)